

## Cross Line Laser Level with stand



## Characteristics

Numbers of beams : 2  
 Maximum span (m) : 30  
 Precision (mm/m) : 0.2  
 Unit of measure : m  
 Temperature in use (°C) : -10/+45  
 Weight (g) : 620

## Norms

☑ IP 54

## Benefits

- Compact, easy to put in a tool box.

## Compliance marks



## GENERAL INFORMATION

## Description

Class II laser level with projections of horizontal and vertical lines intersecting at 90°. Indoor and outdoor use. Supplied with storage pouch and instruction manual.

## Technical details

Shock-absorbing bimaterial rubber casing.  
 'Tilt' mode for angle tracing and marking.  
 Sturdy folding feet for angle positioning and height adjustment.  
 Self-levelling mechanism.  
 Visual and sound 'out of range' alarm.  
 1/4 threading (adapts to tripod BIZ 700 388).  
 Power supply: 3 AA batteries (not supplied).  
 Dimensions: 100 x 82 x 104 mm.  
 Weight: 620 g.

## Application(s)

For the horizontal and vertical alignment of electrical sockets, switches, cables, pipes, worktops, wall coverings, radiator brackets, etc.

## Instructions

1. Use possible outdoors, 50 m range using a detector.

## ACCESSORIES



Tripod for lasers BIZ 700 276, BIZ 782 276 and BIZ 700 394

**LOGISTIC INFORMATION**

**Packaging**



**Cardboard box with window**

Height (cm) : 16,1  
 Length (cm) : 12,9  
 Depth (cm) : 12,6  
 📦 Net weight (kg) : 0,548  
 📦 Gross weight (kg) : 0,548



**Outer package 1**



**Carton box**

Height (cm) : 16,5  
 Length (cm) : 77  
 Depth (cm) : 26,5  
 📦 Net weight (kg) : 6,576  
 📦 Gross weight (kg) : 8,55



x 12.00

**Outer package 2**



**Pallet**

Height (cm) : 114  
 Length (cm) : 120  
 Depth (cm) : 80  
 📦 Net weight (kg) : 157,824  
 📦 Gross weight (kg) : 204,45



x 288.00