



## Gas soldering iron 30 to 125 W



### Benefits

- Gas canister (38 ml for a use during 3 hours and a half average).
- Blow torch function for heatshrink tubes; simply undo the metal ring.

## GENERAL INFORMATION

### Technical details

Equivalent power: 30-125 W.  
Bit temperature: 250-550 °C.

### Instructions

1. Heating time: 15 sec.


## ACCESSORIES



Spare tip with 1.6 mm point



Deflector nozzle for heatshrink sleeving



Spare jet



Heat blower for gas soldering iron

 LOGISTIC INFORMATION

 Packaging



**Blister package**

Height (cm) : 3,4  
 Length (cm) : 30,6  
 Depth (cm) : 10,3  
 Net weight (kg) : 0,15  
 Gross weight (kg) : 0,2



 Outer package 1



**Carton box**

Height (cm) : 31,51  
 Length (cm) : 21,82  
 Depth (cm) : 20  
 Net weight (kg) : 1,8  
 Gross weight (kg) : 2,88



x 12.00

 Outer package 2



**Carton box**

Height (cm) : 35,2  
 Length (cm) : 46,1  
 Depth (cm) : 42,6  
 Net weight (kg) : 7,2  
 Gross weight (kg) : 12,6



x 48.00

 Outer package 3



**Pallet**

Height (cm) : 100  
 Length (cm) : 120  
 Depth (cm) : 82  
 Net weight (kg) : 72  
 Gross weight (kg) : 148,3



x 480.00