



**BIZ'GEL EXPRESS** sealing gel 280 ml cartridge  
*Mono-component ready-to-use injectable gel!*



**Characteristics**

Net volume (ml) : **280**

**Norms**

- ☑ EN 60529
- ☑ IP 68

**Benefits**

- Ready to use.
- Reusable.
- Self-amalgamating.
- Usable immediately at low temperature down to -40 °C!
- No mixing, no waiting time.
- Easily re-accessible.
- Non toxic.
- No shelf-life.

**Compliance marks**



**GENERAL INFORMATION**

**Description**

Injectable and ready-to-use mono-component gel in 280 ml cartridge.

**Technical details**

Dielectric strength: > 23 kV/mm.

Voltage: up to 1 kV.

Installation temperature: -15 °C to +55 °C.

Operating temperature after polymerization: -60 °C to +200 °C.

**Advices**

Use a cartridge gun.

**Application(s)**

Sealing and insulation of electrical connections.

Ideal for watertightness of confined junction boxes, just inject BIZ'GEL EXPRESS regardless of the position of your junction box or connection system.

Ideal solution for watertightness of all junction boxes in your worksites!

**ACCESSORIES**



Heavy duty for cartridges and intumescent foam

**LOGISTIC INFORMATION**

**Packaging**



**Carton box**

Height (cm) : 23,8  
 Length (cm) : 6,4  
 Depth (cm) : 6,4  
 Net weight (kg) : 0,375  
 Gross weight (kg) : 0,375



**Outer package 1**



x 24

**Carton box**

Height (cm) : 26  
 Length (cm) : 27  
 Depth (cm) : 40  
 Net weight (kg) : 9  
 Gross weight (kg) : 9,5



**Outer package 2**



x 576

**Pallet**

Height (cm) : 105  
 Length (cm) : 80  
 Depth (cm) : 120  
 Net weight (kg) : 228  
 Gross weight (kg) : 258

