



# Nylon pull-wire fixed endings pulling eye and flexible head with pulling eye 20 m Ø 4 mm without casing

*Suitable for passing the needle through unencumbered environments.*



## Characteristics

Length (m) : 20  
Pull-wire Ø (mm) : 4  
Breakage (kg) : 70

## Benefits

- Very flexible.
- Low shape memory.

## GENERAL INFORMATION

### Technical details

Hexagonal crimping of sleeves.  
Included:  
Flexible head with M5 threaded Ø 6 mm eyelet (BIZ 700 240).  
M5 threaded Ø 6 mm eyelet (BIZ 700 241).

### Advices

Maximum bending diameter, 4 cm.

### Application(s)

For pulling cables through electrical conduits and ducts from 16 to 25 mm.  
Ideal for pulls longer than 20 m.

## LOGISTIC INFORMATION

### Packaging



#### Color sticker

Height (cm) : 30  
Length (cm) : 30  
Depth (cm) : 3  
Net weight (kg) : 0,305  
Gross weight (kg) : 0,305



### Outer package 1



#### Carton box

Height (cm) : 60  
Length (cm) : 32  
Depth (cm) : 32  
Net weight (kg) : 10,7  
Gross weight (kg) : 11,4



### Outer package 2



#### Pallet

Height (cm) : 113  
Length (cm) : 120  
Depth (cm) : 80  
Net weight (kg) : 128,1  
Gross weight (kg) : 148,7

