

Pullwire polyester mono 15 m Ø 3 mm with dispenser
The go anywhere residential wire-pulling needle!



Characteristics

Length (m) : **15**
Pull-wire Ø (mm) : **3**
Breakage (kg) : **80**

Benefits

- Highly rigid.
- No shape memory.
- Does not rotate on its axis.
- Ultra-slim diameter.

GENERAL INFORMATION

Technical details

Hexagonal crimping of sleeves.
Includes:
Flexible head with crimped M5 Ø 6 mm eyelet (BIZ 700 240).
M5 threaded Ø 6 mm eyelet (BIZ 700 241).
Casing (BIZ 760 058).

Advices

Maximum bending diameter, 2 cm.

Application(s)

For pulling cables through 16 to 50 mm electrical ducts and conduits, even if congested and curved.
Ideal for distances up to 15 m.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 8
Length (cm) : 36
Depth (cm) : 30
Net weight (kg) : 1,17
Gross weight (kg) : 1,17



Outer package 1



Carton box

Height (cm) : 35
Length (cm) : 39
Depth (cm) : 32
Net weight (kg) : 4,68
Gross weight (kg) : 5,33



Outer package 2



Pallet

Height (cm) : 119
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 84,24
Gross weight (kg) : 110,94

