

# Double-sided PE foam tape white 19 mm x 10 m x 0.95 mm



## Characteristics

Colour : **White**  
 Length (m) : **10**  
 Width (mm) : **19**  
 Thickness (mm) : **0.95**

## Benefits

- Suitable for indoor and outdoor use (high resistance to UV, humidity and solvents).
- Excellent performance against shearing.
- Can be torn by hand.

## GENERAL INFORMATION

### Description

Double-sided PE foam tape, solvent acrylic adhesive.

### Technical details

Adhesion at 180° on stainless steel: 12 N/cm.  
 Tensile strength: 65 N/10 mm<sup>2</sup>.  
 Density: 100 kg/m<sup>3</sup>.  
 Operating temperature: -20 °C to +120 °C.  
 Application temperature: +15 °C to +30 °C.  
 Bonding period (at 23 °C): 24 hr.

### Application(s)

Assembly operations for which a good load bearing capacity is required.  
 Hanging mirrors, rods and mouldings.  
 Signs and panels.

## LOGISTIC INFORMATION

### Packaging



#### Plastic film

Height (cm) : 15  
 Length (cm) : 15  
 Depth (cm) : 1,9  
 Net weight (kg) : 0,09  
 Gross weight (kg) : 0,092



3 700420 311157

### Outer package 1



#### Carton box

Height (cm) : 16  
 Length (cm) : 30  
 Depth (cm) : 16  
 Net weight (kg) : 1,02  
 Gross weight (kg) : 1,17



3 700882 190680

x 14.00

### Outer package 2



#### Pallet

Height (cm) : 120  
 Length (cm) : 80  
 Depth (cm) : 120  
 Net weight (kg) : 120  
 Gross weight (kg) : 130



3 700882 190697

x 1428.00