

## Double grip tape black 25 mm x 2 m x 5.4 mm



### Characteristics

Length (m): 2  
 Width (mm): 25  
 Thickness (mm): 5.4

### Benefits

- No drill required.
- Re-openable.
- Convenient roll format.
- Excellent resistance to humidity.



## GENERAL INFORMATION

### Description

Strong adhesive tape coated with plastic studs which interlock when pressed.

This system can be used for invisible, openable and re-usable attachments.

The double tape guarantees a reliable and fast attachment with no need for a drill.

### Technical details

Maximum load resistance: 3.5 kg/cm<sup>2</sup>.

Stud density per cm<sup>2</sup>: 42.

Resistance to temperature: -30 to +90 °C.

Installation temperature: +15 to +30 °C.

### Advices

Optimal grip after 36 hours.

### Application(s)

Workshop set-up, installation of panels to access cables, attach cable trays, office equipment, etc.

### Instructions

1. Clean grease and dust carefully from the surfaces.
2. Cut 2 strips to the required length.
3. Apply strong pressure to the strips for 30 seconds.
4. Press the 2 strips together and make sure you hear a click guaranteeing a secure grip.
5. To open, separate the 2 strips by pulling.

**LOGISTIC INFORMATION**

**Packaging**



**Carton box**

Height (cm) : 25  
 Length (cm) : 14,5  
 Depth (cm) : 14,5  
 Net weight (kg) : 0,09  
 Gross weight (kg) : 0,11



**Outer package 1**



x 10

**Carton box**

Height (cm) : 30  
 Length (cm) : 15,5  
 Depth (cm) : 15,5  
 Net weight (kg) : 1,1  
 Gross weight (kg) : 1,24



**Outer package 2**



x 1700

**Pallet**

Height (cm) : 155  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 210,8  
 Gross weight (kg) : 220,8

