



SQUALE mini S4 for sealed connection up to 3 conductors and wire 4 mm² (x 8)



Characteristics

Capacity 1 conductor (mm²): 1-4
 Capacity 2 conductors (mm²): 1-4
 Dimensions (mm): 61 x 18
 Quantity per box : 8

Norms

- ☑ EN 50393 ; EN 60529
- ☑ IP X8

Benefits

- Quick repair of your damaged cables.
- Non toxic.

Compliance marks



GENERAL INFORMATION

Description

Connector's sealing cover for wires with a section up to 4 mm².
 Connection system not included.

Technical details

Pre-filled with neutral insulating gel.
 Installation temperature (°C): -40 to +50.
 Operating temperature (°C): 90.
 Maximum cable diameter (mm): 10.

Application(s)

Ensures quick and safe sealing of your connections.
 Ideal in outdoor, damp or immersed environments when it is a cable protected by the cable outer sheath installed in the SQUALE MINI (up to 3 m).
 Ideal in outdoor and in a derivation box when wires are not protected by a cable outer sheath.

Instructions

1. 1. Make your connection using a block or a connection terminal.
2. 2. Insert your connection into the SQUALE MINI.
3. 3. Close the SQUALE MINI, check that the gel slightly protrudes from the SQUALE MINI by winding the wires and/or the cable.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 11
 Length (cm) : 12
 Depth (cm) : 7
 Net weight (kg) : 0,28
 Gross weight (kg) : 0,28



Outer package 1



Carton box

Height (cm) : 44
 Length (cm) : 50
 Depth (cm) : 38
 Net weight (kg) : 28
 Gross weight (kg) : 28,6



x 100.00

Outer package 2



Pallet

Height (cm) : 105
 Length (cm) : 80
 Depth (cm) : 120
 Net weight (kg) : 228,8
 Gross weight (kg) : 260



x 800.00