



# 5 way lever push-in wire connector for rigid and flexible wire (x 50)



## Characteristics

Number of inputs : **5**  
 Length (mm) : **21**  
 Width (mm) : **24.5**  
 Height (mm) : **11.7**  
 Quantity per pot : **50**

## Norms

EN 60998-1:2004 ;  
 EN 60998-2-2:2004

## Benefits

- Connection of rigid wires without activating the release lever.
- Viewing window for visual inspection of the clamping points means greater safety during installation.

## Compliance marks



## GENERAL INFORMATION

### Description

Clamping connectors for solid, rigid stranded and flexible wires.

### Technical details

Glow wire test: 960 °C.  
 Clamping range: 0.2 mm<sup>2</sup> to 2.5 mm<sup>2</sup> for solid, rigid stranded and flexible wires.  
 Material: polycarbonate.  
 Copper connection system.  
 Voltage: 450 V.  
 Intensity: 24 A.  
 Strip off 10 mm.

### Instructions

#### Flexible wires:

1. Strip off the wire at 10 mm.
2. Lift the levers.
3. Put the wires in the connector.
4. Lower the levers.

#### Solid wires:

1. Strip off the wire at 10 mm.
2. Direct insertion of the stripped solid wires in the connector (closed levers).

## ADDITIONAL INFORMATION

Rated temperature: 85 °C.

## ACCESSORIES





Automatic stripping pliers 0.02 to 10 mm<sup>2</sup>

 LOGISTIC INFORMATION

 Packaging



**Bucket**



Height (cm) : 10  
 Length (cm) : 7,5  
 Depth (cm) : 7,5  
 Net weight (kg) : 0,207  
 Gross weight (kg) : 0,242



 Outer package 1



**Carton box**

Height (cm) : 13  
 Length (cm) : 39,1  
 Depth (cm) : 16,5  
 Net weight (kg) : 2,42  
 Gross weight (kg) : 2,58





x 10

 Outer package 2



**Carton box**

Height (cm) : 53  
 Length (cm) : 39,5  
 Depth (cm) : 17  
 Net weight (kg) : 10,32  
 Gross weight (kg) : 10,55





x 40

 Outer package 3



**Pallet**

Height (cm) : 120  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 295,4  
 Gross weight (kg) : 320,4



x 1120