

**Plastic plug Ø 5 x 25 mm (x 20)**  
*One single plug for all walls, all uses!*



**Characteristics**

Ø (mm) : 5  
 Length (mm) : 25  
 Tensile strength (kg) : 8  
 Shear resistance concrete 25N/mm (daN\*) : 40  
 Quantity : 25  
 Selling unit : Un

**Materials**

☑ Solid materials

**Benefits**

- Very easy to apply thanks to their low tightening torque.
- Shorter plugs for quick attachment.

**GENERAL INFORMATION**

**Technical details**

Nylon plastic plug.  
 25 plugs squares.

**Application(s)**

For light (chutes, lights, etc.) and medium (electrical panels, cabinets, etc.) attachments in all types of supports: solid, hollow, soft and hard.

**Instructions**

1. Drill the support to the indicated diameter.
2. Insert the plug.
3. Expand the plug by screwing
4. The plug is expanded and in position.

**LOGISTIC INFORMATION**

**Packaging**



**Plastic box**

Height (cm) : 13  
 Length (cm) : 8,7  
 Depth (cm) : 8,7  
 Net weight (kg) : 0,18  
 Gross weight (kg) : 0,25



**Outer package 1**



**Carton box**

Height (cm) : 14  
 Length (cm) : 27,5  
 Depth (cm) : 27,5  
 Net weight (kg) : 1,62  
 Gross weight (kg) : 2,5



**Outer package 2**



**Pallet**

Height (cm) : 113  
 Length (cm) : 113  
 Depth (cm) : 80  
 Net weight (kg) : 90,72  
 Gross weight (kg) : 159,78

