

BIZ'GEL EXPRESS sealing gel 280 ml cartridge
Mono-component ready-to-use injectable gel!



Characteristics

Net volume (ml) : **280**

Norms

- ☑ EN 60529
- ☑ IP 68

Benefits

- Ready to use.
- Reusable.
- Self-amalgamating.
- Usable immediately at low temperature down to -40 °C!
- No mixing, no waiting time.
- Easily re-accessible.
- Non toxic.
- No shelf-life.

Compliance marks



GENERAL INFORMATION

Description

Injectable and ready-to-use mono-component gel in 280 ml cartridge.

Technical details

Dielectric strength: > 23 kV/mm.

Voltage: up to 1 kV.

Installation temperature: -15 °C to +55 °C.

Operating temperature after polymerization: -60 °C to +200 °C.

Advices

Use a cartridge gun.

Application(s)

Sealing and insulation of electrical connections.

Ideal for watertightness of confined junction boxes, just inject BIZ'GEL EXPRESS regardless of the position of your junction box or connection system.

Ideal solution for watertightness of all junction boxes in your worksites!

ACCESSORIES



Heavy duty for cartridges and intumescent foam

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 23,8
 Length (cm) : 6,4
 Depth (cm) : 6,4
 Net weight (kg) : 0,375
 Gross weight (kg) : 0,375



Outer package 1



x 24

Carton box

Height (cm) : 26
 Length (cm) : 27
 Depth (cm) : 40
 Net weight (kg) : 9
 Gross weight (kg) : 9,5



Outer package 2



x 576

Pallet

Height (cm) : 105
 Length (cm) : 80
 Depth (cm) : 120
 Net weight (kg) : 228
 Gross weight (kg) : 258

