

## Black high performance vinyl tape 19 mm x 20 m x 0.18 mm



## Characteristics

Biz references : **BIZ 225 033**  
 Colour : **Black**  
 Length (m) : **20**  
 Width (mm) : **19**  
 Thickness (mm) : **0.18**  
 Quantity : **1**

## Norms

EN 60454 &  
 ☉ IEC60454-3-1-7/F-  
 PVCP/90

## Benefits

- High resistance to extreme temperatures.
- UV resistant.
- No feathering.



## GENERAL INFORMATION

## Description

High performance electrical vinyl tape.  
 Synthetic rubber adhesive mass.  
 Flexible, press-on adhesive tape.  
 High resistance to sunshine, water, oil, acid, alkali and corrosive chemicals.  
 Flame-retardant/Self-extinguishing.  
 Lead free.

## Technical details

Dimensions: 19 mm x 20 m x 0.18 mm.  
 Tensile strength: 32 N/cm.  
 Elongation at break: 240 %.  
 Adhesion to steel 2B: 2.25 N/cm.  
 Adhesion to backing: 2.15 N/cm.  
 Dielectric strength: 40 kV/mm.  
 Insulation resistance:  $5.0 \times 10^9 \Omega/25 \text{ mm}$ .  
 Operating temperature: -18 °C to +105 °C.  
 Application temperature: -10 °C to +40 °C.  
 Color: black.

## Advices

For making cable harnesses, apply the product with at least a 50 % covering.

## Application(s)

Implementation of cable harnesses, splicing, wire and cable terminations.  
 Repairing conduits.  
 Electrical insulation at high and low temperatures.  
 Suitable for outdoor use, UV-resistant.

ZOOM ON PRODUCT



LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm) : 2,3  
Length (cm) : 9,6  
Depth (cm) : 9,6  
Net weight (kg) : 0,09  
Gross weight (kg) : 0,11



Outer package 1



x 100

Carton box

Height (cm) : 25  
Length (cm) : 52  
Depth (cm) : 22  
Net weight (kg) : 11  
Gross weight (kg) : 11,2



Outer package 2



x 2000

Pallet

Height (cm) : 115  
Length (cm) : 125  
Depth (cm) : 80  
Net weight (kg) : 224  
Gross weight (kg) : 244

