

Digital clamp meter 600 V



Compliance marks



GENERAL INFORMATION

■ Description

Comes with LCD display and one 9 V battery.

■ Technical details

Display: LCD 4000 measurements.

AC power: 50/60 Hz (AAC).

TRMS.

Voltage bandwidth: AC 50/60 Hz (VAC).

Operating temperature: -10 °C to +50 °C.

Storage temperature: -30 °C to +60 °C.

Relative humidity: 90% (0 °C to 30 °C), 75% (30 °C to 40 °C), 45% (40 °C to 50 °C).

Operating altitude (m): 3000.

Storage (m): 10,000.

Overvoltage: category III 600 V.

Battery: one 9 V battery.

Automatic shut-off: after approx. 35 min.

Dimensions (mm): 229 x 80 x 49.

Weight (g): 303.

Safety: for indoor use and overvoltage category II, pollution degree 2.

Category II includes local level, appliances, portable equipment, etc. with transient overvoltages than overvoltage category III.

LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 25
 Length (cm) : 14
 Depth (cm) : 6
 Net weight (kg) : 0,303
 Gross weight (kg) : 0,573



Outer package 1



Carton box

Height (cm) : 45
 Length (cm) : 33
 Depth (cm) : 52
 Net weight (kg) : 17,2
 Gross weight (kg) : 18,2



x 30.00

Outer package 2



Pallet

Height (cm) : 119
 Length (cm) : 120
 Depth (cm) : 90
 Net weight (kg) : 109,2
 Gross weight (kg) : 130,2



x 180.00