

Tester Voltage 600 V



Characteristics

Safety standard : **CAT III 690V/CAT IV 600 V**
Voltage detection AC/DC (V) : **6V-690VAC/DC**
Frequency (Hz) : **50/60**

Norms

☑ IP 65

Compliance marks



GENERAL INFORMATION

Description

Measures direct and alternating currents.
Displays three-phase AC voltage.
Measures frequency.
RCD test.
Continuity test.
Connector test.
Test in case of dead battery.

Technical details

- Rotation test (three-phase AC): voltage range 57 V-400 V and frequency range 50 Hz to 60 Hz.
- Operating temperature range (°C): -15 to +45 .
- Storage temperature range (°C): -20 to +60.
- Working humidity range: ≤ 85% RH.
- Overvoltage protection class: CAT III 690 V CAT IV 600 V.
- Cleanliness code: 2.
- Safety rules IP65 EN61010-1 EN61243-3 (2010).
- Weight (g): 295 (including batteries).
- Dimensions (mm): 272 x 85 x 31.
- IEC LR03 (AAA) batteries (x 2).
- Automatic-ranging: full range.
- Illumination: full range.
- Low battery voltage indicator (V): approx. 2.4.
- Over-range indicator (V): approx. 755.
- Auto standby mode: standby current < 10 µA.
- Silent mode: full interval.
- Backlight: full range.
- LCD screen (voltage): 6 V~ 690 V.
- LCD screen (frequency): 40 Hz~400 Hz.

LOGISTIC INFORMATION

Packaging



Blister package

Height (cm) : 4,8
 Length (cm) : 35,5
 Depth (cm) : 17
 Net weight (kg) : 0,34
 Gross weight (kg) : 0,43



Outer package 1



Carton box

Height (cm) : 36,5
 Length (cm) : 41,5
 Depth (cm) : 38
 Net weight (kg) : 9,3
 Gross weight (kg) : 10



x 20.00

Outer package 2



Pallet

Height (cm) : 124
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 150
 Gross weight (kg) : 165



x 300.00